



TWEETE **HYH-201** TWEETE **HYH-328** DRIVER **HYH-3402** DRIVER **HYH-3408N**

产品型号 MODEL	HYH-201	HYH-328	HYH-3402	HYH-3408N
标称直径 Nominal Diameter	φ 68mm	φ 98mm	φ 100mm	φ 85mm
喉口直径 Exit Throat Diameter	/	/	1"	1"
音圈直径 Voice Coil Diameter	φ 19.5mm	φ 14.28mm	φ 34.4mm	φ 34.4mm
额定阻抗 Rated Impedance	4 ohms	4 ohms	8 ohms	8 ohms
灵敏度 Sensitivity(1W/1M)	90dB	101dB	106 dB	110 dB
额定功率 Power Capacity	8W	20W	40W	50W
频率范围 Frequency Range	150Hz-20Khz	1KHz-20KHz	1KHz-20KHz	1.2KHz-20KHz
共振频率 Resonance Frequency	150Hz	1KHz	1.2KHz	1.5KHz
产品净重 Net weight	0.1Kg	0.3Kg	1.1Kg	0.7Kg



DRIVER **HYH-4403A** DRIVER **HYH-4408N** DRIVER **HYH-4405N**

产品型号 MODEL	HYH-4403A	HYH-4408N	HYH-4405N
标称直径 Nominal Diameter	φ 100mm	φ 95mm	φ 100mm
喉口直径 Exit Throat Diameter	1"	1"	1"
音圈直径 Voice Coil Diameter	φ 44.4mm	φ 44.4mm	φ 44.4mm
额定阻抗 Rated Impedance	8 ohms	8 ohms	8 ohms
灵敏度 Sensitivity(1W/1M)	106 dB	118 dB	117 dB
额定功率 Power Capacity	60W	80W	60W
频率范围 Frequency Range	1KHz-19KHz	1KHz-20KHz	1KHz-20KHz
共振频率 Resonance Frequency	1.2KHz	1.1KHz	1.5KHz
产品净重 Net weight	1.5Kg	1.1Kg	1.5Kg



DRIVER **HYH-3806** DRIVER **HYH-4401** DRIVER **HYH-4402** DRIVER **HYH-4403**

产品型号 MODEL	HYH-3806	HYH-4401	HYH-4402	HYH-4403
标称直径 Nominal Diameter	φ 100mm	φ 140mm	φ 120mm	φ 100mm
喉口直径 Exit Throat Diameter	1"	1"	1"	1"
音圈直径 Voice Coil Diameter	φ 38mm	φ 44.4mm	φ 44.4mm	φ 44.4mm
额定阻抗 Rated Impedance	8 ohms	8 ohms	8 ohms	8 ohms
灵敏度 Sensitivity(1W/1M)	108 dB	110 dB	108 dB	105 dB
额定功率 Power Capacity	60W	80W	80W	60W
频率范围 Frequency Range	1.2KHz-30KHz	900Hz-19KHz	1KHz-20KHz	1KHz-18KHz
共振频率 Resonance Frequency	1.5KHz	1KHz	1.2KHz	1.2KHz
产品净重 Net weight	1Kg	3.2Kg	2.1Kg	1.5Kg



DRIVER **HYH-4506** DRIVER **HYH-5101** DRIVER **HYH-6501**

产品型号 MODEL	HYH-4506	HYH-5101	HYH-6501
标称直径 Nominal Diameter	φ 120mm	φ 134mm	φ 156mm
喉口直径 Exit Throat Diameter	1"	1"	1.4"
音圈直径 Voice Coil Diameter	φ 44.4mm	φ 51.5mm	φ 65.5mm
额定阻抗 Rated Impedance	8 ohms	8 ohms	8 ohms
灵敏度 Sensitivity(1W/1M)	115dB	105 dB	108 dB
额定功率 Power Capacity	100W	60W	80W
频率范围 Frequency Range	1KHz-20KHz	1KHz-19KHz	1KHz-19KHz
共振频率 Resonance Frequency	1.2KHz	1.2KHz	1.2KHz
产品净重 Net weight	2.1Kg	2.8Kg	3.8Kg





DRIVER **HYH-7501**



DRIVER **HYH-7502N**



DRIVER **HYH-7505**

产品型号	MODEL	HYH-7501	HYH-7502N	HYH-7505
标称直径	Nominal Diameter	φ 170mm	φ 131mm	φ 170mm
喉口直径	Exit Throat Diameter	1.4"	1.4"	1.4"
音圈直径	Voice Coil Diameter	φ 75.5mm	φ 75.5mm	φ 75.5mm
额定阻抗	Rated Impedance	8 ohms	8 ohms	8 ohms
灵敏度	Sensitivity(1W/1M)	115 dB	118 dB	118 dB
额定功率	Power Capacity	100W	110W	120W
频率范围	Frequency Range	700Hz-19KHz	500Hz-19KHz	500Hz-19KHz
共振频率	Resonance Frequency	900Hz	760Hz	750Hz
产品净重	Net weight	4.5Kg	2.6Kg	4.5Kg



WOOFER **HYM-T401**



WOOFER **HYM-L605**



WOOFER **HYM-L801N**

产品型号	MODEL	HYM-T401	HYM-L605	HYM-L801N
标称直径	Nominal Diameter	Φ 137mm	Φ 165mm	Φ 230mm
音圈直径	Voice Coil Diameter	φ 25.5mm	φ 35.5mm	φ 49.5mm
额定阻抗	Rated Impedance	8 ohms	8 ohms	8 ohms
灵敏度	Sensitivity(1W/1M)	93dB	98dB	98dB
额定功率	Power Capacity	50W	120W	200W
频率范围	Frequency Range	95Hz-7.5KHz	76Hz-6.5KHz	65Hz-4.3KHz
共振频率	Resonance Frequency	95Hz	76Hz	65Hz
BL 因数	BL factor	10.335T	11.965T	12.5T
机械品质因数	Qms	4.36	4.893	3.7
电品质因数	Qes	0.325	0.342	0.37
总品质因数	Qts	0.29	0.32	0.33
等效空气容积	Vas	5.163Ltr	8.060Ltr	12.5Ltr
机械顺性	Cms	196.192 uM/N	294.091 uM/N	113.132 uM/N
产品净重	Net weight	1.1Kg	2.8Kg	2.2Kg



WOOFER **HYL-L806**



WOOFER **HYL-L1001**



WOOFER **HYL-T1005**

产品型号	MODEL	HYL-L806	HYL-L1001	HYL-T1005
标称直径	Nominal Diameter	Φ 210mm	Φ 261mm	Φ 258mm
音圈直径	Voice Coil Diameter	φ 49.55mm	φ 75.5mm	φ 49.55mm
额定阻抗	Rated Impedance	8 ohms	8 ohms	4 ohms
灵敏度	Sensitivity(1W/1M)	94dB	96dB	94dB
额定功率	Power Capacity	150W	400W	150W
频率范围	Frequency Range	70Hz-5.5KHz	28Hz-270HZ	35Hz-4KHz
共振频率	Resonance Frequency	70Hz	28Hz	36Hz
BL 因数	BL factor	14.507T	17.2T	8.567T
机械品质因数	Qms	1.681	7.3	3.345
电品质因数	Qes	0.41	0.42	0.36
总品质因数	Qts	0.329	0.38	0.325
等效空气容积	Vas	12.627Ltr	46Ltr	112.998Ltr
机械顺性	Cms	180.964 uM/N	142.113 uM/N	603.739 uM/N
产品净重	Net weight	3.5Kg	7.2Kg	3.2Kg



WOOFER **HYL-L1006**



WOOFER **HYL-L1018**



WOOFER **HYL-T1022**

产品型号	MODEL	HYL-L1006	HYL-L1018	HYL-T1022
标称直径	Nominal Diameter	Φ 260mm	Φ 262mm	Φ 257mm
音圈直径	Voice Coil Diameter	φ 65.5mm	φ 65.5mm	φ 49.55mm
额定阻抗	Rated Impedance	8 ohms	8 ohms	8 ohms
灵敏度	Sensitivity(1W/1M)	96dB	95dB	95dB
额定功率	Power Capacity	200W	250W	150W
频率范围	Frequency Range	54Hz-6.5KHz	52Hz-4.5KHz	48Hz-6.5KHz
共振频率	Resonance Frequency	54Hz	52Hz	48Hz
BL 因数	BL factor	15.443T	23.244T	10.535T
机械品质因数	Qms	1.827	2.05	1.557
电品质因数	Qes	0.239	0.243	0.298
总品质因数	Qts	0.212	0.217	0.25
等效空气容积	Vas	48.281Ltr	29.251Ltr	71.183Ltr
机械顺性	Cms	257.964 uM/N	156.284 uM/N	402.311 uM/N
产品净重	Net weight	4.6Kg	5.8Kg	3.4Kg



HYL SERIES HYL LOW FREQUENCY TRANSDUCERS



WOOFER HYL-L1201N



WOOFER HYL-L1202N



WOOFER HYL-L1203

产品型号	MODEL	HYL-LI201N	HYL-LI202N	HYL-LI203
标称直径	Nominal Diameter	Φ316mm	Φ316mm	Φ318mm
音圈直径	Voice Coil Diameter	φ75.5mm	φ75.5mm	φ85.5mm
额定阻抗	Rated Impedance	8 ohms	8 ohms	8 ohms
灵敏度	Sensitivity(1W/1M)	100dB	99dB	99dB
额定功率	Power Capacity	350W	350W	400W
频率范围	Frequency Range	48HZ-2.3KHZ	50HZ-2.1KHZ	56HZ-3.4KHZ
共振频率	Resonance Frequency	48Hz	50Hz	56Hz
BL 因数	BL factor	25.5T	20.1T	19.2T
机械品质因数	Qms	3.7	4.2	2.5
电品质因数	Qes	0.17	0.21	0.27
总品质因数	Qts	0.16	0.2	0.25
等效空气容积	Vas	76Ltr	73Ltr	52Ltr
机械顺性	Cms	118.132 uM/N	116.112 uM/N	122.278 uM/N
产品净重	Net weight	4.9Kg	4.0Kg	7.5Kg



WOOFER HYL-L1205



WOOFER HYL-L1206



WOOFER HYL-L1207

产品型号	MODEL	HYL-LI205	HYL-LI206	HYL-LI207
标称直径	Nominal Diameter	Φ316mm	Φ315mm	Φ315mm
音圈直径	Voice Coil Diameter	φ75.5mm	φ75.5mm	φ75.5mm
额定阻抗	Rated Impedance	8 ohms	8 ohms	8 ohms
灵敏度	Sensitivity(1W/1M)	100dB	98dB	99dB
额定功率	Power Capacity	350W	300W	350W
频率范围	Frequency Range	50HZ-3.5KHZ	54HZ-3.6KHZ	56HZ-4KHZ
共振频率	Resonance Frequency	50Hz	54Hz	56Hz
BL 因数	BL factor	19.1T	24.595T	18.410T
机械品质因数	Qms	6.7	1.772	2.312
电品质因数	Qes	0.23	0.21	0.27
总品质因数	Qts	0.2	0.188	0.242
等效空气容积	Vas	66Ltr	50.104Ltr	45.124Ltr
机械顺性	Cms	108.313 uM/N	119.559 uM/N	116.270 uM/N
产品净重	Net weight	6.9Kg	6.9Kg	7.1Kg

HYL SERIES HYL LOW FREQUENCY TRANSDUCERS



WOOFER HYL-L1215



WOOFER HYL-L1275



WOOFER HYL-L1301

产品型号	MODEL	HYL-LI215	HYL-LI275	HYL-LI301
标称直径	Nominal Diameter	Φ315mm	Φ322mm	Φ359mm
音圈直径	Voice Coil Diameter	φ75.5mm	φ99.3mm	φ75.5mm
额定阻抗	Rated Impedance	8 ohms	8 ohms	8 ohms
灵敏度	Sensitivity(1W/1M)	99dB	100dB	99dB
额定功率	Power Capacity	350W	400W	380W
频率范围	Frequency Range	59HZ-3KHZ	61HZ-2.3KHZ	48HZ-3KHZ
共振频率	Resonance Frequency	59Hz	61Hz	48Hz
BL 因数	BL factor	18.75T	24.993T	19.3T
机械品质因数	Qms	1.741	1.446	3.1
电品质因数	Qes	0.207	0.207	0.27
总品质因数	Qts	0.185	0.181	0.25
等效空气容积	Vas	72.697Ltr	39.052Ltr	73Ltr
机械顺性	Cms	168.291 uM/N	90.403 uM/N	127.311 uM/N
产品净重	Net weight	7.3Kg	11.6Kg	8.2Kg



WOOFER HYL-L1302



WOOFER HYL-L1303N



WOOFER HYL-L1503N

产品型号	MODEL	HYL-LI302	HYL-LI303N	HYL-LI503N
标称直径	Nominal Diameter	Φ359mm	Φ359mm	Φ394mm
音圈直径	Voice Coil Diameter	φ75.5mm	φ75.5mm	φ75.5mm
额定阻抗	Rated Impedance	8 ohms	8 ohms	8 ohms
灵敏度	Sensitivity(1W/1M)	99dB	101dB	101dB
额定功率	Power Capacity	380W	380W	400W
频率范围	Frequency Range	48HZ-3KHZ	50HZ-3.3KHZ	40HZ-2KHz
共振频率	Resonance Frequency	48Hz	50Hz	40Hz
BL 因数	BL factor	19.3T	24.6T	25.5T
机械品质因数	Qms	3.3	3.2	4.3
电品质因数	Qes	0.31	0.25	0.23
总品质因数	Qts	0.28	0.23	0.22
等效空气容积	Vas	75Ltr	80Ltr	130Ltr
机械顺性	Cms	127.383 uM/N	126.436 uM/N	142.316 uM/N
产品净重	Net weight	8.2Kg	5.5Kg	5.6Kg



HYL SERIES HYL LOW FREQUENCY TRANSDUCERS



WOOFER HYL-L1505



WOOFER HYL-L1506



WOOFER HYL-L1507

产品型号	MODEL	HYL-L1505	HYL-L1506	HYL-L1507
标称直径	Nominal Diameter	Φ402mm	Φ395mm	Φ395mm
音圈直径	Voice Coil Diameter	φ75.5mm	φ75.5mm	φ75.5mm
额定阻抗	Rated Impedance	8 ohms	8 ohms	8 ohms
灵敏度	Sensitivity(1W/1M)	99dB	100dB	100dB
额定功率	Power Capacity	300W	400W	400W
频率范围	Frequency Range	44Hz-2.5KHz	48Hz-2.5KHz	49Hz-2.8KHz
共振频率	Resonance Frequency	44Hz	48Hz	49Hz
BL 因数	BL factor	14.839T	19.909T	19.896T
机械品质因数	Qms	2.029	2.101	2.056
电品质因数	Qes	0.461	0.26	0.247
总品质因数	Qts	0.375	0.232	0.221
等效空气容积	Vas	239.233Ltr	142.205Ltr	159.732Ltr
机械顺性	Cms	230.301 uM/N	145.516 uM/N	150.096 uM/N
产品净重	Net weight	8.2Kg	7.4Kg	7.5Kg

HYL SERIES HYL LOW FREQUENCY TRANSDUCERS



WOOFER HYL-L1802



WOOFER HYL-L1808



WOOFER HYL-L8CXN

产品型号	MODEL	HYL-L1802	HYL-L1808	HYL-L8CXN
标称直径	Nominal Diameter	Φ465mm	Φ460mm	Φ240mm
音圈直径	Voice Coil Diameter	φ99.3mm	φ99.3mm	φ50.5mm
额定阻抗	Rated Impedance	8 ohms	8 ohms	8 ohms
灵敏度	Sensitivity(1W/1M)	99dB	99dB	96dB
额定功率	Power Capacity	600W	600W	200W
频率范围	Frequency Range	25Hz-1.5KHz	23Hz-1.5KHz	80Hz-20KHz
共振频率	Resonance Frequency	25Hz	23Hz	80Hz
BL 因数	BL factor	25T	20.569T	10.963T
机械品质因数	Qms	6.5	2.986	4.787
电品质因数	Qes	0.29	0.39	0.389
总品质因数	Qts	0.27	0.345	0.36
等效空气容积	Vas	340Ltr	621.782Ltr	15.183Ltr
机械顺性	Cms	197.321uM/N	282.904uM/N	207.539uM/N
产品净重	Net weight	13.3Kg	13.3Kg	5.1Kg



WOOFER HYL-L1508



WOOFER HYL-L1517



WOOFER HYL-L1801

产品型号	MODEL	HYL-L1508	HYL-L1517	HYL-L1801
标称直径	Nominal Diameter	Φ395mm	Φ387mm	Φ465mm
音圈直径	Voice Coil Diameter	φ99.3mm	φ99.3mm	φ125mm
额定阻抗	Rated Impedance	8 ohms	8 ohms	8 ohms
灵敏度	Sensitivity(1W/1M)	99dB	99dB	101dB
额定功率	Power Capacity	600W	500W	850W
频率范围	Frequency Range	49Hz-1.8KHz	35Hz-2KHz	28Hz-1KHz
共振频率	Resonance Frequency	49Hz	35Hz	28Hz
BL 因数	BL factor	29.359T	21.827T	27.484T
机械品质因数	Qms	1.563	1.363	3.343
电品质因数	Qes	0.277	0.393	0.373
总品质因数	Qts	0.235	0.305	0.336
等效空气容积	Vas	75.37Ltr	202.104Ltr	118.316Ltr
机械顺性	Cms	69.143 uM/N	166.729uM/N	53.833uM/N
产品净重	Net weight	12.3Kg	12.6Kg	20Kg



WOOFER HYL-L10CXN



WOOFER HYL-L12CXN



WOOFER HYL-L15CXN

产品型号	MODEL	HYL-L10CXN	HYL-L12CXN	HYL-L15CXN
标称直径	Nominal Diameter	Φ262mm	Φ320mm	Φ390mm
音圈直径	Voice Coil Diameter	φ65.5mm	φ75.5mm	φ75.5mm
额定阻抗	Rated Impedance	8 ohms	8 ohms	8 ohms
灵敏度	Sensitivity(1W/1M)	98dB	100dB	102dB
额定功率	Power Capacity	300W	400W	500W
频率范围	Frequency Range	65Hz-20KHz	55Hz-19KHz	45Hz-19KHz
共振频率	Resonance Frequency	65Hz	55Hz	45Hz
BL 因数	BL factor	13.838T	16.915T	16.94T
机械品质因数	Qms	5.883	8.48	5.847
电品质因数	Qes	0.233	0.26	0.314
总品质因数	Qts	0.224	0.252	0.298
等效空气容积	Vas	59.973Ltr	67.988Ltr	191.727Ltr
机械顺性	Cms	332.631uM/N	159.789uM/N	180.16uM/N
产品净重	Net weight	6.5Kg	9.9Kg	12.5Kg

